

ADHESIVE SELECTION CHART

RUBBER FLOORING

Z100

Adhesive	Recommended for:	Benefits	Rolling Loads	Recommended Trowel & Spread Rate*	Surface Moisture	VOC Compliant Floorscore	Anti-Microbial
#10 Acrylic Latex	Sustain and Flex 2.5 and 3.5mm tile Sustain and Flex 6.0 and 9.0mm in non-sport or low impact applications	Easy to use. Excellent Green Grab	Periodic use of Carts, Hospital beds and other moderate loads. Not for use where castered chairs are regularly used.	-2.5mm thickness or less -150 ft ² / Gallon -1/32 x 1/16 x 1/16 U-notch trowel	Low	Zero VOC FloorScore	Yes
#15 Two Part Urethane	Sustain and Flex 6.0 and 9.0 applications. Sustain and Flex 2.5 and 3.5mm	Excellent for high traffic and moderate surface moisture	Regular use castered chairs and heavy rolling loads including forklifts.	-3.5mm or greater thickness -100 ft ² / Gallon -1/16 x 1/16 x 1/16 square notch trowel	Moderate Locker Rooms, Bathrooms Cafeterias Entries	Zero VOC FloorScore	Yes
#25 Releasable	Sustain and Flex 6.0 and 9.0mm tile over access panels.	Releasable	Not for use where heavy rolling loads are frequent	-1/16 x 1/16 x 1/16 square notch trowel -100 ft ² / Gallon	Low	Zero VOC Floorscore	Yes

Sport Products: Use of #15 two part urethane is highly recommended for best performance in applications where exercise activities and sports occur or where free weights and exercise equipment are present. This also includes areas subjected to high lateral or vertical stresses. While Zandur Sport products provide a reasonable level of sub-floor protection, drop off mats are required where free weights are used to provide additional protection.

* **Trowel Recommendations and Adhesive Spread Rate:** These are recommendations based upon normal installation conditions and correct use of application tools and in no way guarantee actual rates of coverage.

Cork Flooring: Use #40 Contact adhesive only