

Pro-Coat® Aqua-Pro™ is an aliphatic waterborne urethane copolymer. With the use of new polymerization technology. This chemistry yields a product that can be used as a single component or two component. This coating exhibits outstanding adhesion over a wide range of substrates. Its properties include great durability, outstanding scuff and scratch resistance. Aqua-Pro is recommended for residential, sport and commercial applications.

Use: Interior & Exterior Wood Projects

Sheens: Matte, Satin, Semi-Gloss, Gloss

Coats: 3 coats (additional coat can be applied)

Ingredients: Waterborne Urethane, Acrylic resin

Dry Time: 1-3 Hours

Cure Time: 75% - 24 hours, 90% - 72 hours, 100% cure - 7 day

Shelf Life: 1 year unopened container

Clean-Up: Water

Coverage: 500 - 600 sqft per gallon

Thinning: Water (Up to 4 ounces per gallon)

Pot Life: 12 hours after mixing crosslinker (Pro-link 2 oz. crosslinker)

Application: T-bar, Spray, Pad, Brush, Roller

Spray Tip Size Recommended: Compressed Air .040, Hvp .043-.051, Airless .009 -.013, Air cap should be medium size.

Recommended Uses: Ideal for Commercial, High-End Residential, Cork, and Sport Flooring

Clarity: Clear

Defoaming: Excellent

Leveling: Excellent

Odor: Non Offensive

pH: 7.8

Density: 8.60 lbs./gallon

VOC < 200 grams per liter

Solids: 33%

Viscosity: 25 second #2 Zahn cup

Flash Point: N/A

Surface Preparation:

Note: Do not use over other products or sealers containing stearates. Surface must be cleaned and prepared by appropriate NOFMA accepted sanding methods. Prior to coating application, remove all dust from floor and surrounding structures. NEW FLOORS – are ready for coating after above procedures are completed. RECOATING – existing surfaces must be evaluated and compatibility determined by the applicator.

Application:

CAUTION! MIX WELL BEFORE APPLYING. AFTER MIXING COATING, LET SIT WITH LID VENTED FOR 15-20 MINUTES OR UNTIL ANY MIXING FOAM HAS DIMINISHED. Aqua-Pro™ may be applied by T-bar application, foam applicators, roller or spray. If applied by roller, roll at moderate speed to prevent foaming. Apply three (3) uniform coats. For best performance avoid thick coats, achieve proper coverage per gallon. BEFORE RECOATING, allow to dry at least 2-3 hours, abrade floor properly, vacuum and tack floor before applying succeeding coats.

General:

Covers 500 – 600 sqft per gallon (First coat may achieve less coverage)

Dries to touch in 25 to 60 minutes

Do not apply on damp days or when surface temperature is below 40°F.

Clean-Up tools with soap and water

Maintenance:

Put walk-off mats at all entrance doorways to keep out excessive dirt and grit.

Apply padding on bottom of legs of furniture that can cause pre-mature wear or damage.

Sweep or vacuum daily and damp mop as needed with Pro-Coat® Pro-Care™ Citrus Hardwood Floor Cleaner.