

TECHNICAL DATA

PRAXIS SOLID CORK FLOORING

Z606

Finishes: Commercial Factory Applied Polyurethane, Unfinished (special order)

Description	Test Standard	Product Line
		Praxis Solid Cork
Limited Wear Warranty		8-30 years. Refer to Zandur warranty Z002 for details
Critical Radiant Flux	ASTM E648	Class II
Smoke Density	ASTM E662	<340 pass
Coefficient of Friction	ASTM D2047 - Dry	0.75
	ASTM D2047 - Wet	0.65
Acoustical Behavior STC	ASTM E90-09 6" slab, no ceiling	52dB
Acoustical Behavior IIC	ASTM E2179-03 6" Slab, no ceiling	50 dB
Delta IIC (effect of flooring on IIC)	ASTM E2179-03	22dB
Slip Coefficient exceeds UL and ADA Recommendations		Yes
Static Load Limit / PSI	ASTM F970	Pass
Chemical Resistance	ASTM F925	Excellent ¹
Bacterial Resistance	ASTM G21	Resistant
CHPS Indoor Air Quality Compliant	CA 01350	Yes
Meets Test Required for Floor Score Certification	CA 01350	Yes
Resistance to Cigarette Burns	DIN 519611984	Yes
Forklift Traffic		No
Oil and Grease Resistance		No
Suitability for Castered Chairs		Yes

* Refer to current Zandur sample binder for availability of thickness and dimensions in specific patterns.

1. Detailed test results may be obtained from Zandur..
2. Note: Above test results are from specific materials. Variance from above values may occur due to minor batch variances.