

Technical Data

Praxis Solid Cork Flooring

		Product Line
Description	Test Standard	Praxis Solid Cork – Polyurethane Finished
Limited Wear Warranty		10 years 3/16" 15 years 5/16" 30 years 1/2" 8 years veneer patterns Refer to Zandur warranty Z002 for details
Critical Radiant Flux	ASTM E648	Class II
Smoke Density	ASTM E662	<450 Pass
Coefficient of Friction	ASTM D2047 - Dry	0.75
	ASTM D2047 - Wet	0.65
Acoustical Behavior STC	ASTM E90-09 6" slab, no ceiling	52dB
Acoustical Behavior IIC	ASTM E2179-03 6" Slab, no ceiling	50 dB
Delta IIC (effect of flooring on IIC)	ASTM E2179-03	22dB
Noise Reduction Coefficient (NRC)	ASTM C423	0.05
Slip Coefficient exceeds UL and ADA Recommendations		Yes
Static Load Test	ASTM F970	0.008" at 24 hrs
Chemical Resistance	ASTM F925	Excellent ¹
Bacterial Resistance	ASTM G21	Does Not Promote Mold Growth
CHPS Indoor Air Quality Compliant	CA 01350	Yes
Meets Test Required for Floor Score Certification	CA 01350	Yes
Forklift Traffic		No
Oil and Grease Resistance		No
Suitability for Castered Chairs		Not recommended. Use of chair mats suggested.
Standard Specification for Cork Floor Tile	ASTM F3008-13	Meets/Exceeds Specification

* Refer to zandur.com for availability of thickness and dimensions in specific patterns.

1. Detailed test results may be obtained from Zandur.

2. Note: Above test results are from specific materials. Variance from above values may occur due to natural product variances.